


GUM ROSIN (WG GRADE)



General Information

Chemical Formula	C ₂₀ H ₃₀ O ₂	
Synonym	Colophony	
Origin	Indonesia	
H.S. Code	3806.10.00	
CAS No.	8050-09-7	
Molecular Weight	302.44 g mol ⁻¹	

Application

Rubber	It is used for softening of rubber and to ease the dispersion of filler in rubber.
Adhesive	It is used to prepare rubber and synthetic resin based adhesive.
Pulp and Paper	It is used as a paper sizing agent to improve the quality and strength of paper.
Paint	It is used in paints to provide smoothness to the coated surface.
Ink	It is used in the manufacture of ink to act as a carrier of ink and to increase its adhesion to paper.
Other applications	In soap industry as replacement of aliphatic acid, food industry for chewing gum, insulator, welding flux, etc.

Specification

Property	Units	Value
Color by lovibond comparator		WG
Softening point ring and ball	°C	76 (min)
Impurity / Solubility in Toluene	%	0.07 (max)
Acid Value		160 – 190
Saponification value		170 – 220
Iodine value		5 – 25
Ash content	%	0.05 (max)
Volatile oil content	%	2.5 (max)

Packaging

- 80 @ 240 kg Used Iron/Steel Drum, 19.2 MT / 20'FCL

Tradeasia International Pte Ltd
133 Cecil Street # 12-03 Keck Seng Tower
Singapore 069535
Republic Of Singapore
Tel : +65 6227 6365
Fax : +65 6225 6286
Email : contact@chemtradeasia.com